

Heat-Shrinkable tubes



APPLICATIONS



SELECTION GUIDE

Reference	Ratio	Designation
POLYOLEFIN AND PVC - THIN WALL TUBINGS		
GTR-102	2:1	+105°C, Heat - Shrinkable tubing in PVC, shiny surface
GTR-103	2:1	+125°C, Heat - Shrinkable tubing in polyolefin, UL 224 VW-1
GTR-104	2:1	+125°C, Heat - Shrinkable tubing in polyolefin, in MINIBOX
GTR-105	2:1	+135°C, Heat - Shrinkable tubing in polyolefin, UL 224 VW-1
GTR-106	3:1	+125°C, Heat - Shrinkable tubing in polyolefin, UL 224 VW-1
POLYOLEFIN - DUAL WALL TUBINGS (WITH ADHESIVE)		
GTR-202	3:1	+125°C, Heat - Shrinkable tubing in polyolefin with adhesive
GTR-203	4:1	+125°C, Heat - Shrinkable tubing in polyolefin with adhesive
OTHER THIN WALL AND SPECIAL TUBINGS		
GTR-301	2:1	+175°C, Heat - Shrinkable tubing in KYNAR, UL 224 VW-1
GTR-302	2:1	+190°C, Heat - Shrinkable tubing in KYNAR
GTR-303	2:1	+200°C, Heat - Shrinkable tubing in fluoroelastomer VITON, UL 224 VW-1
GTR-304	4:1	+260°C, Heat - Shrinkable tubing in PTFE
MEDIUM AND HEAVY WALL TUBINGS		
GTR-401	4:1	+125°C, Medium wall heat - shrinkable tubing
GTR-402	4:1	+125°C, Heavy wall heat - shrinkable tubing
GTR-403	4:1	+125°C, Medium wall heat - shrinkable tubing with adhesive
GTR-404	4:1	+125°C, Heavy wall heat - shrinkable tubing with adhesive
GTR-405	6:1	+110°C, Heat - shrinkable tubing with adhesive
MEDIUM VOLTAGE PRODUCTS		
GTR-501	2:1	+105°C, Heat Shrinkable tubing for medium voltage BUS-BAR of medium thickness - 24 kV
GTR-502	2:1	+105°C, Heat Shrinkable tubing for medium voltage BUS-BAR of high thickness - 36kV
MOULDED PARTS		
GTR-601	3:1	+100°C, Adhesive-lined heat shrinkable end cap