

Polyester braided sleeving with polyurethane varnish



CHARACTERISTICS

- Temperature class : F
- Continuous working temperature : from -30°C to +155°C. Peaks at +185°C
- Dielectric strength : 4kV
- Halogen free
- Flammability : combustible
- Very good mechanical resistance
- Good resistance to hydrocarbon
- Resistance to transformer oils
- Good compatibility with impregnation varnishes of the same class
- Good behaviour with liquid combustibles, no decomposition
- Watertight
- Very flexible

STANDARDS*

- Compliant with RoHS directive
- Compliant with Reach regulation
- EN (CEI) 60684-3
- EN 60684-1 (10-2003)
- EN 60684-2 (07-2012)

COLOURS AND PACKAGINGS

- Manufactured diameters : From 0.5 to 12 mm
- Standard colour : White
- Other colours : Green, blue, red, black, orange, yellow

Standard packaging :

- Diameter 0.5 mm : 400 m
- Diameter 0.8 to 1.5 mm : 300 m
- Diameter 2 to 6 mm : 200 m
- Diameter 7 to 12 mm : 100 m

APPLICATIONS



Inner diameter (mm)	0.5	0.8	1	1.5	2	2.5	3	3.5	4	4.5	5	6	7	8	9	10	12
Tolerance inner diameter (± mm)	0.15	0.2	0.2	0.2	0.2	0.2	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.5	0.5	0.5	0.5

* Our products pass all or parts of requirements for the above-mentioned standards. The technical information written on our datasheets correspond to the most recent knowledges we have on those products, but the user is not exempted to verify the performances in the real particular context of application.