

Fireproof sleeving braided fibre glass coated with silicone rubber stitched with nylon Velcro



CHARACTERISTICS

- Temperature class : C
- Continuous working temperature : from -60°C to +260°C
- Can resist to melting glass projection at +1200°C.
- Good resistance to :
 - » presence of flames
 - » projection of metals or melting glass
 - » occasional very high temperature
 - » projection of vapour
- Excellent flexibility at low temperatures
- Slight swelling can be caused by hydrocarbons
- Good resistance to UV
- Asbestos free
- Fireproof
- Self Extinguishing
- Heat Insulating

STANDARDS*

- Compliant with RoHS directive
- Compliant with Reach regulation
- HL1 and HL2 compliant according to railway standard EN45545
- EN (CEI) 60684-3 sheets 400 to 402 (02/2003)
- EN 60684-1 (10-2003)
- EN 60684-2 (07-2012)
- EN 60695-2 -11 (09/2014)

COLOURS AND PACKAGINGS

- Manufactured diameters : From 15 to 120 mm
- Standard color : Brick red

Standard packaging :
• Rolls of 15 or 20 meters

APPLICATIONS



* Our products pass all or parts of requirements for the above mentioned standards. The technical information written on our datasheets correspond to the most recent knowledges we have on those products, but the user is not exempted to verify the performances in the real particular context of application.