

Extruded PVC sleeving



APPLICATIONS



STANDARDS*

- Compliant with RoHS directive
- Compliant with Reach regulation
- EN 60684-1 (10-2003)
- EN 60684-3 sheets 100 to 105 (12/2003)
- Compliant with SHVC (list published by the ECHA)

Characteristics	Temperature class	Minimum temperature	Maximum temperature	Dielectrical strength	Density	Hardness	Resistance at break	Elongation at break	Good mechanical resistance
Unit		°C	°C	kV/mm	g/cm ³	ShA	N/mm ²	%	
Test method						ISO 868	ISO 527	ISO 527	
PVC 105*	B	-20	+105	10 to 20	1.39 ±0.02	83 ±2	≥13	≥280	Yes

Characteristics	Cold flex	Thermal stability congo red	Watertight	Very flexible	Manufactured diameters	Colours	Packaging	Anti-rat treatments	Self-extinguishing version
Unit	°C	Minutes			mm				
Test method	ISO 458	CEI 20-34/3-2							
PVC 105*	-25 ±2	≥250	Yes	Yes	1 to 30	All colours	On request	On request	On request

* Our products pass all or parts of requirements for the above-mentioned standards. The technical information written on our datasheets correspond to the most recent knowledges we have on those products, but the user is not exempted to verify the performances in the real particular context of application.